

# Remover

**SYNTEKO**<sup>®</sup>  
exceptional floor finishes

Preparation



**Synteko Remover 1692** is an alkaline detergent which efficiently removes dirt, soil and old coats of polish. Use before sanding and recoating with Synteko floor finishes or new treatment with Synteko maintenance products.

## DIRECTIONS FOR USE

Vacuum well, wet mop with the solution and allow to work in for a few minutes. Scrub during this work-in period. Follow with a damp mop with clean water. Further treatment with 10% vinegar in water is recommended if screening and recoating will be performed.

**Mixture:** Normal cleaning: 1 part of Synteko Remover per 100 parts of water  
Heavy soilage: 2 – 3 parts of Synteko Remover per 100 parts of water

## TECHNICAL DATA

**Base:** Cat- and non-ionic tensides, complex formers, alkali, perfume and water

**Color:** Pale green

**Density:** 1000-1150 kg/m<sup>3</sup> (8.3 – 9.5 lbs/gal)

**pH:** Concentrated 10.5 – 11.5

## SAFETY PRECAUTIONS AND HANDLING

Classified as: Irritating to eyes and skin. Handling: Maintain good industrial hygiene standard. Use gloves. In case of eye contact rinse immediately with plenty of water and get medical attention. **Keep out of reach of children.** For further information check our MSDS (Material Safety Data Sheet).

## OTHER DATA

**Mixture:** Normal cleaning: 1 part of Synteko Remover per 100 parts of water  
Heavy soilage: 2 – 3 parts of Synteko Remover per 100 parts of water

**Storage:** 36 months in a closed container

**Packing:** 1 L **Keep from freezing!**



DISCLAIMER: Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us. Date: 5/02